

IN THE CLAIMS

Please amend the claims as follows:

1-9. (Cancelled)

10. (Currently Amended) A computer-readable medium containing computer instructions and data for carrying out the operations steps of:

associating ~~a value of a setting~~ each of a plurality of setting values for a presentation device with each of a plurality of media input ~~devices having media input~~ signals in a multimedia system;

selecting one of said media input signals for presentation ~~to a user of said system;~~

modifying said one media input signal in accordance with one of said setting values, wherein said one setting value is associated with said one media input signal;

transmitting said modified one media input signal to said presentation device; and

presenting said one media input signal to said user with the said presentation device having the value of said setting associated with a corresponding media input device.

11. (Currently Amended) A medium according to claim 10, wherein said associating operation step further associates a plurality of settings with each of said media input ~~devices~~ signals.

12. (Currently Amended) A medium according to claim 11, further comprising a data structure for holding said values for all of said settings, said structure having a separate entry for each of said media input ~~device~~ signal.

13. (Currently Amended) A medium according to claim 10, wherein said method further comprises:

receiving a modification command ~~from said user;~~ and

modifying the value of said setting for only said one media ~~devices~~ signals.

14. (Currently Amended) A method for controlling a multimedia system configured to receive a plurality of multimedia input signals ~~from input devices~~ and present media from at least one of said input signals ~~to a user~~ through at least one output device, said method comprising:

selecting one of said signals in response to a selection command to said system;

retrieving, from a table of parameter entries associated with ~~an input device~~

~~providing~~ said signals, at least one value of a parameter ~~for controlling said output device~~ and corresponding to said one selected signal; and

modifying said one signal in accordance with said at least one retrieved parameter value;

transmitting said one signal to said output device;

presenting media from said one signal to said output device ~~in accordance with at least one retrieved parameter value.~~

15. (Original) A method according to claim 14, wherein each of said parameter entries holds multiple values each corresponding to a different presentation of media from said signals.

16. (Original) A method according to claim 15, wherein a first group of said parameter entries controls the presentation of media from a first output device, and a second group of said parameter entries controls the presentation of media from a second output device.

17. (Currently Amended) A method according to claim 14, wherein said selecting step comprises:

receiving a selection code ~~from said user~~ representing said one signal; and

switching said one input signal to said one output device.


18. (Currently Amended) A method according to claim 14, comprising the further steps of:

receiving a parameter code for modifying the value of said parameter for only a particular one of said input devices;

producing a modified value of said parameter in response to said code;

storing said modified parameter value in an entry of said table corresponding to said particular one input signal ~~device~~; and

thereafter, presenting media from said selected signal to said output device in accordance with said modified parameter value.

 19. (Previously Presented) A method according to claim 18, wherein said particular one signal is said one of said signals currently selected in response to said selection command.

20. (Currently Amended) A method according to claim 18, wherein said parameter code is received from ~~said~~ a user.

21. (Currently Amended) A method according to claim 18, wherein each of said table entries holds multiple values each corresponding to a different one of a plurality of parameters associated with the presentation of media from said input signals ~~devices~~ .

22. (Original) A method according to claim 21, wherein said parameter code further specifies a particular one of said parameters as said parameter to be modified.

23-27. (Previously Cancelled)

28. (Currently Amended) A multimedia system for receiving a plurality of media signals from a plurality of media devices and producing an output signal derived from one of said input signals ~~to a user~~ on an output device for said system, said system comprising:

~~a user~~ an input device responsive to ~~said user~~ a selection for selecting said one input signal;

a switch for transmitting a selected one of a plurality of media signals to said output device in response to said selection command;

a table having a plurality of entries each holding a value of at least one parameter of said output signal, different ones of said entries being associated with different ones of said media signals ~~devices~~ ;

a processor responsive to said selection command for accessing one of said values from said table, said one value being in an entry corresponding to said selected one input signal; and

an output controller coupled to said output device for setting said at least one parameter of said output signal in accordance with said one value.

29. (Currently Amended) A multimedia system according to claim 28, wherein said ~~user~~ input device is a keyboard having a number of buttons for producing said selection command.

30. (Previously Presented) A multimedia system according to claim 29, wherein said system includes a data processor coupled to said output device for presenting signals to be presented thereon, and wherein said keyboard also includes an array of data-entry keys for the data processor.

31. (Previously Presented) A multimedia system according to claim 28, wherein said input device is further adapted to produce a parameter modification command, and wherein said table is adapted to store a modified value of said parameter in one of said table entries so as to affect the value of said parameter only for one of said media signals associated with said one table entry.

32. (Previously Presented) A multimedia system according to claim 31, wherein said input device has a number of buttons for producing said parameter-modification command.

33. (Currently Amended) A multimedia system according to claim 32, wherein said input device is coupled to said system by a wireless link such that said parameter-modification command can be performed by said a user from a position from which said output device is normally viewed.

34. (Previously Presented) A multimedia system according to claim 32, wherein the parameter of said output signal is at least one of the group comprising an audio volume, bass, treble, and balance.

DL
Cont
35. (Previously Presented) A multimedia system according to claim 32, wherein the parameter of said output signal is at least one of the group comprising video brightness, contrast, color, tint, and sharpness.

36. (Previously Presented) A multimedia system according to claim 32, further comprising an output device coupled to said output signal.

37. (Previously Presented) A multimedia system according to claim 32, wherein said output device includes a video monitor.

38. (Previously Presented) A multimedia system according to claim 32, wherein said output device includes a sound system.

39. (Previously Presented) A multimedia system according to claim 32, further comprising at least one media device from the group comprising a TV tuner, a direct satellite receiver, a DVD player, a video tape recorder, a CD player, and a MIDI port.

40. (Currently Amended) A multimedia system comprising:

- a plurality of media devices, each providing a different media signal;
- a presentation device having parameters for controlling the presentation of media signals received from the media devices;
- ~~a user~~ an input device responsive to ~~said user~~ a selection for selecting a media device and media signal from the media device;
- a switch coupled to the media devices and presentation device, wherein said switch is for transmitting a selected one of the media signals to the presentation device in response to the selection command;
- a table having a plurality of entries each holding values of the parameters for the presentation device based on the media device providing the media signal;
- a processor responsive to said selection command, wherein said processor is for accessing said values from said table, said values being in an entry corresponding to the media device providing the selected media signal; and
- an output controller coupled to said output device for applying the values to the presentation device such that the media signal is presented in accordance with the parameters.


41. (Currently Amended) A multimedia system comprising:

- a plurality of media devices, each providing a different media signal;
- a presentation device having parameters for controlling the presentation of media signals received from the media devices;
- ~~a user~~ an input device responsive to ~~said user~~ a selection for selecting a media device and media signal from the media device;
- a switch coupled to the media devices and presentation device, wherein said switch is for transmitting a selected one of the media signals to the presentation device in response to the selection command;
- a table having a plurality of entries each holding values of a parameter for the presentation device based on the media device providing the media signal;

a processor responsive to said selection command, wherein said processor is for accessing ~~said~~ a value from said table, said value being in an entry corresponding to the media device providing the selected media signal; and

an output controller coupled to said output device for applying the value to the presentation device such that the media signal is presented in accordance with the parameters.

42. (Currently Amended) A multimedia system ~~comprising~~ that receives media signals from a plurality of different types of media devices and provides such signals to a presentation device for presentation of media signals received from the media devices comprising:

 a ~~user~~ an input device responsive to ~~said user~~ a selection for selecting a media device and media signal from the media device;

a table having a plurality of entries each holding values of parameters for controlling the presentation device based on the media device providing the media signal;

a processor responsive to said selection command, wherein said processor is for accessing said values from said table, said values being in an entry corresponding to the media device providing the selected media signal; and

an output controller coupled to said output device for applying the values to the presentation device such that the media signal is presented in accordance with the parameters.

43. (New) A medium according to claim 10, wherein said transmitting is performed by a switch.

44. (New) A medium according to claim 10, wherein said selecting is performed by a switch in response to a channel-control signal.

45. (New) A medium according to claim 10 further containing computer instructions and data for carrying out the operations of:

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.111

Serial Number: 09/002990

Filing Date: January 5, 1998

Title: INDIVIDUALIZED PARAMETER CONTROL FOR MULTIPLE MEDIA SOURCES IN A DATA PROCESSING SYSTEM

Page 9
Dkt: 450.219US1

D1
and storing said one setting in a parameter controller, wherein said parameter controller performs said modifying.
